

CATERPILLAR DE33E0



GENERAL SET DATA

ENGINE REF:	CAT C3.3
ALTERNATOR REF:	R1555L4
STANDARD CONTROL PANEL:	EMCP 4.1
OPTIONAL CONTROL PANEL:	N/A

OUTPUT

FREQUENCY:	50 hz
VOLTAGE:	400/230
PRIME POWER:	30 kVA
STANDBY POWER:	33 kVA

DIMENSIONS

OPEN MODEL

LENGTH:	1540 mm
WIDTH:	970 mm
HEIGHT:	1361 mm
DRY WEIGHT:	838 Kg
FUEL TANK CAPACITY:	-

CLOSED MODEL

LENGTH:	-
WIDTH:	-
HEIGHT:	-
DRY WEIGHT:	-
FUEL TANK CAPACITY:	-
ACOUSTIC PRESSURE AT 1M:	-
ACOUSTIC PRESSURE AT 7M:	-

CATERPILLAR DE33E0

TECHNICAL DATA

GENERAL ENGINE DATA

MANUFACTURER:	CAT
MODEL REF:	C3.3
SPEED:	1500 RPM
POWER PRP:	24 kWm
POWER LTP:	26.4 kWm
NUMBER OF CYLINDERS:	3
DISPLACEMENT:	3.3 L
BORE:	105 mm
STROKE:	127 mm
COMPRESSION RATIO:	19.25
COOLING SYSTEM:	WATER
AIR INLET SYSTEM:	NATURAL
OIL CAPACITY:	8.3 L
EXHAUST GAS TEMP:	520 °C
EXHAUST GAS FLOW:	5.8 m ³ /min

ALTERNATOR DATA

ALTERNATOR REF:	R1555L4
INSULATION CLASS:	H
INDICATION OF PROTECTION:	IP23

FUEL

CONSUMPTION AT 100%:	6.9 L/hr
CONSUMPTION AT 75%:	5.2 L/hr
CONSUMPTION AT 50%:	3.8 L/hr

TERMS & CONDITIONS

The equipment meets the following standards: IEC60034-1, IEC60034-22, ISO3046, ISO8528, NEMA MG 1-32, NEMA MG 1-33, 2004/108/EC, 2006/42/EC, 2006/95/EC.